



LT Soldering Tip Family

- + Designed for universal applications
- + Universal SMT & THT jobs
- + A wide range of low cost tips
- + Solid copper plated with iron for maximum durability and long life



| | Article | a / b (mm) / (inch) | Article | a / b (mm) / (inch) | Article | a / b (mm) / (inch) |
|-------------------------|--|---|---|---|------------------------------|--|
| Chisel | LT 1SC T0054449499 | 0.4 mm / 0.15 mm 0.016 inch / 0.006 inch | LT B T0054440599 | 2.4 mm / 0.8 mm 0.094 inch / 0.031 inch | LT HX T0054442099 | 0.8 mm / 0.4 mm 0.031 inch / inch |
| | LT 1SCNW T0054449799 | 0.3 mm / 0.1 mm 0.012 inch / 0.004 inch | LT BSL T0054451799 | 2.4 mm / 0.45 mm 0.094 inch / 0.018 inch | LT K T0054443899 | 1.2 mm / 0.4 mm 0.047 inch / 0.016 inch |
| | LT 4X T0054442899 | 1.2 mm / 0.4 mm 0.047 inch / 0.016 inch | LT BX T0054444299 | 2.4 mm / 0.8 mm 0.094 inch / 0.031 inch | LT L T0054441499 | 2.0 mm / 1.0 mm 0.079 inch / 0.034 inch |
| | LT A T0054444099 | 1.6 mm / 0.7 mm 0.063 inch / 0.028 inch | LT C T0054440799 | 3.2 mm / 0.8 mm 0.126 inch / 0.031 inch | LT M T0054442599 | 3.2 mm / 1.2 mm 0.126 inch / 0.047 inch |
| | LT ALX T0054444399 | 1.6 mm / 0.7 mm 0.063 inch / 0.028 inch | LT D T0054440999 | 4.6 mm / 0.8 mm 0.181 inch / 0.031 inch | LT MX T0054446999 | 3.2 mm / 1.2 mm 0.126 inch / 0.047 inch |
| | LT ASL T0054451699 | 1.6 mm / 0.45 mm 0.063 inch / 0.018 inch | LT DLL T0054444899 | 4.6 mm / 1.2 mm 0.181 inch / 0.047 inch | LT MX2 T0054451299 | 3.0 mm / 1.0 mm 0.118 inch / 0.034 inch |
| | LT AX T0054442799 | 1.6 mm / 0.8 mm 0.063 inch / 0.031 inch | LT H T0054443799 | 0.8 mm / 0.4 mm 0.031 inch / 0.016 inch | | |
| Conical long | LT 1L T0054442399 | 0.2 mm 0.008 inch | LT O T0054448199 | 0.8 mm 0.031 inch | | |
| | LT 1LNW T0054449899 | 0.1 mm 0.004 inch | LT S T0054440699 | 0.4 mm 0.016 inch | | |
| | LT 1LX T0054442499 | 0.2 mm 0.008 inch | LT T T0054448299 | 0.6 mm 0.024 inch | | |
| Round | Round | | Round tip sloped 45° | | | |
| | LT 1 T0054443599 | 0.25 mm 0.01 inch | LT 4 T0054443999 | 1.2 mm 0.047 inch | | |
| | LT 1A T0054448999 | 0.5 mm 0.02 inch | LT BB 45 T0054448499 | 2.4 mm 0.094 inch | | |
| | LT 1S T0054443699 | 0.2 mm 0.008 inch | LT DD 45 T0054447899 | 4.0 mm 0.157 inch | | |
| | LT 1SA T0054448899 | 0.5 mm 0.02 inch | LT DD 45 T0054448699 | 4.6 mm 0.181 inch | | |
| | LT 1SNW T0054449699 | 0.1 mm 0.004 inch | LT F T0054440899 | 1.2 mm 0.047 inch | | |
| | LT 1X 30° T0054442599 | 0.4 mm 0.016 inch | LT 22CP T0054440873 | 2.0 mm 0.079 inch | | |
| | LT AS T0054440499 | 1.6 mm 0.063 inch | LT 33CP T0054440877 | 3.0 mm 0.118 inch | | |
| | LT BS T0054449999 | 2.0 mm 0.079 inch | Round sloped 60° | | | |
| | LT CS T0054441199 | 3.2 mm 0.126 inch | LT AA 60° T0054448799 | 1.6 mm 0.063 inch | | |
| Measuring tip | LT Measuring tip T0054441699 | 0.5 mm 0.02 inch | Gullwing | LT GW1 T0054441099 | 1.4 mm 0.055 inch | |
| Adapter | LT Adapter T0054412199 | | LT Screw in tip M4 T005444499 | | LT GW2 T0054451199 | 3.5 mm 0.138 inch |
| | | | Knife | LT KN T0054447999 | 2.0 mm 0.079 inch | |
| | | | | LT KN5L 45° T0054451999 | 2.0 mm 0.079 inch | |

Silver Line

Heat up time
 °C
 -350
 -300
 -200
 -100
 -0
10 Sec.*

Component size
 S TO M

*from 50°C to 350°C / 120°F to 620°F



| Article | a / b (mm) / (inch) |
|-----------------------------------|----------------------|
| Round tip sloped 60° | |
| LT BB 60 T0054444499 | 2.4 mm 0.094 inch |
| LT CC 60 T0054444599 | 3.2 mm 0.126 inch |
| Round tip slim bent | |
| LT 1SLX 30° T0054442699 | 0.4 mm 0.016 inch |

Weller®

weller-tools.com/toolselector/en
 weller-tools.com/toolselector/us